



## GENERAL APPLICATIONS

**Ecotorch®** is designed as a superior modified bitumen torch-applied roofing membrane (with appropriate base sheet or interply sheets) for flashing, new roofing, and re-roofing applications. It's also an ideal membrane for repair of built-up roofing membranes. See MBTechnology Specification Manual for installation instructions.

## STORAGE

Store rolls on end in a dry location. Keep materials clean and away from excessive heat. Do not lay flat. Keep materials off of the ground. Store on pallets or similar (pallets should not be stored more than two high without protective bracing). Cover rolls with opaque tarp.


Store in areas where temperature is between 50° F and 90° F.

## WARRANTIES

**Ecotorch G** (Granules) carries a 12-year limited material warranty. Workmanship guarantees are available for MBTechnology "eligible contractors." Material warranties and workmanship guarantees require materials be installed in compliance with the recommendations contained in the MBTechnology specification manual. Incorporating Ecotorch S (Smooth) as an underlayer can extend the warranty to 20 years.

## Technical Specification (Nominal)

PRODUCT NAME	<b>ecotorch G</b>	<b>ecotorch S</b>
REINFORCEMENT	Polyester mat	Polyester mat
APPLICATION	Heat weld	Heat weld
COVERAGE	1 Square	1 Square
WEIGHT PER ROLL (LBS.)	102	85
SURFACING	Granules (8 colors available)	Smooth
ASTM REFERENCE	ASTM 6164 Type-G	ASTM 6164 Type-S



Since 1983, MBTechnology has provided quality roofing and underlayment systems to vendors throughout the nation.

**MBTECHNOLOGY**  
SUPERIOR ROOFING & UNDERLAYMENT SYSTEMS

188 South Teilman Ave, Fresno CA 93706-1334 - 559-233 2181  
Technical Hotline: 800-621 9281 FAX: 559-233 4607  
www.mbtechnology.com info@mbtechnology.com